



TARA PAINTS & CHEMICALS

(An ISO 9001:2015, 18001:2007 Certified Company)

India

A/423/4, Mahagujrat Industrial Estate, Sarkhej Bavla Rd, NH 8A, Village, Moraiya, Gujarat 382213, INDIA
Customer care : +91 8000011774, email : customercare@tarapaints.com, web: www.taralac.com

North America

3106- A, Bethel Road , Upper Chichester – PA 19061
OFFICE : 484 474 0278 EMAIL : karan@tarapaints.com

2310 EPOXY HARDENER - WW SAFETY DATA SHEET

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY/UNDERTAKING

Product Information

Trade name: Epoxy Hardener Water White

2. HAZARDS IDENTIFICATION

Emergency Overview

Human health hazards: Product is toxic and harmful if inhaled. Maybe moderately toxic if swallowed. Slightly toxic and may be harmful if absorbed through the skin. May be corrosive to the eyes. May be corrosive to the skin. May be corrosive to the respiratory tract. Corrosive to mouth, throat, and stomach. May produce CNS depression. May cause skin sensitization.

Safety hazards: Corrosive. The material will not burn unless preheated.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS – No.	Weight %
Cycloaliphatic amine	*	
Proprietary Component	*	
Phenolic Compound	*	

*The specific chemical identity/proportion of this component is considered trade secret information under 29 CFR 1910.1200

4. FIRST AID MEASURES

Inhalation: Do not attempt to rescue the victim unless proper respiratory protection is worn. Remove victim to fresh air and provide oxygen if breathing is difficult. Get medical attention.

Skin contact: Immediately remove contaminated clothing. Flush with large amounts of water for at least 15 minutes. Flush exposed skin with water and follow by washing with soap if available. Transport to the nearest medical facility for additional treatment.

Eye contact: Immediately flush eyes with plenty of water for 15 minutes while holding eyelids open. Transport to the nearest medical facility for additional treatment.



TARA PAINTS & CHEMICALS

(An ISO 9001:2015, 18001:2007 Certified Company)

India

A/423/4, Mahagujrat Industrial Estate, Sarkhej Bavla Rd, NH 8A, Village, Moraiya, Gujarat 382213, INDIA
Customer care : +91 8000011774, email : customercare@tarapaints.com, web: www.taralac.com

North America

3106- A, Bethel Road , Upper Chichester – PA 19061
OFFICE : 484 474 0278 EMAIL : karan@tarapaints.com

Ingestion:

Do not induce vomiting. Have victim rinse out the mouth with water, then drunk sips of water to remove the taste from mouth. Do not give liquids to a drowsy, convulsing or unconscious person. If vomiting occurs spontaneously, keep head below hips to prevent aspiration. Get medical attention.

Notes to physician

Symptoms:

Lung damage (scarring, bronchitis, emphysema) may be evidenced by shortness of breath, especially on exertion, and may be accompanied by a chronic cough. Repeated skin contact may result in an allergic skin reaction causing itching, burning, redness, and swelling.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing Media:

Use water fog, "alcohol foam", dry chemical or carbon dioxide.

Water fog may cause frothing which can be violent, especially if sprayed into containers of hot or burning liquid.

Specific hazards during Fire fighting:

DANGER. Corrosive. The material will not burn unless preheated. Delayed lung damage (pulmonary oedema) can be experienced after exposure to combustion products, sometimes hours after the exposure. Nitrogen oxides and other potentially hazardous nitrogen-containing compounds may be released upon combustion.

Evacuate the area of all non-essential personnel. Container areas exposed to direct flame contact should be cooled with large quantities of water as needed to prevent weakening of container structure. Cool fire exposed containers with water.

Special protective equipment for fire-fighters:

Do not enter confined fire space without full bunker gear (helmet with face shield, bunker coats, gloves, and rubber boots) including a positive pressure NIOSH approved self-contained breathing apparatus.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions:

Corrosive.
May burn although not readily ignitable.
Remove ignition sources.
Prevent all bodily contact with spilt materials.
Use cautious judgment when cleaning up large spills.
Shut off leaks, if possible without personal risk.

Environmental precautions:

Dike and contain.
Contain run-off and dispose of properly.



TARA PAINTS & CHEMICALS

(An ISO 9001:2015, 18001:2007 Certified Company)

India

A/423/4, Mahagujrat Industrial Estate, Sarkhej Bavla Rd, NH 8A, Village, Moraiya, Gujarat 382213, INDIA
Customer care : +91 8000011774, email : customer@tarapaints.com, web: www.taralac.com

North America

3106- A, Bethel Road , Upper Chichester – PA 19061
OFFICE : 484 474 0278 EMAIL : karan@tarapaints.com

Neutralize contaminated area as appropriate for acid or base spill.
Prevent from entering into drains, ditches or rivers.

Clean-up methods – small:

Soak up with an absorbent such as clay, sand or other suitable material.
Place in non-leaking container.
Seal tightly for proper disposal.

Clean-up methods – large:

Remove with vacuum trucks or pump to storage/salvage vessels.
Soak up residue with an absorbent such as clay, sand, or other suitable material.
Place in non-leaking container.
Seal tightly for proper disposal.
Flush area with water to remove trace residue.

Additional advice:

Notify authorities if any exposures to the general public or environment occur or are likely to occur. See Section 13 for information on disposal.

7. HANDLING AND STORAGE

Handling

Advice on safe handling:

Do not get in eyes, on the skin or clothing. Do not taste or swallow. Do not breathe material. Use only with adequate ventilation. Avoid contact with skin, eyes, and clothing. Wash thoroughly after handling. Heating this curing agent above 300 Deg. F in the presence of air may cause slow oxidative decomposition; above 500 Deg. F, polymerization may occur. Some epoxy resins can produce exothermic reactions which in large masses can cause runaway polymerization and charring of the reactants. Fumes and vapours from these thermal and chemical decompositions vary widely in composition and toxicity. DANGER. May be corrosive to the eyes. May be corrosive to the skin. Corrosive to the digestive tract. Toxic and harmful if inhaled. Slightly toxic and may be harmful if absorbed through the skin. Maybe moderately toxic if swallowed. May be corrosive to the respiratory tract. May cause CNS depression. May cause skin sensitization. Wash with soap and water before eating, drinking, smoking, applying cosmetics, or using toilet facilities. Launder contaminated clothing before reuse. Contaminated leather articles, including shoes, cannot be decontaminated and should be destroyed to prevent reuse. Do not pressurize drum containers to empty them. Do not breathe fumes. Use a NIOSH-approved respirator as required to prevent overexposure. In accord with 29 CFR.1910.134, use either an atmosphere-supplying respirator or an air-purifying respirator for organic vapours. Containers, even those that have been emptied, can contain hazardous product residues.

Storage

Requirements for storage areas and containers:

Store in a cool, dry place with adequate ventilation.
Keep away from open flames and high temperatures.
Keep containers closed when not in use.



TARA PAINTS & CHEMICALS

(An ISO 9001:2015, 18001:2007 Certified Company)

India

A/423/4, Mahagujrat Industrial Estate, Sarkhej Bavla Rd, NH 8A, Village, Moraiya, Gujarat 382213, INDIA
Customer care : +91 8000011774, email : customercare@tarapaints.com, web: www.taralac.com

North America

3106- A, Bethel Road , Upper Chichester – PA 19061
OFFICE : 484 474 0278 EMAIL : karan@tarapaints.com

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

- Protective measures:** Wear an appropriate respirator and full-body protective clothing.
- Engineering measures:** Adequate ventilation to control airborne concentrations.
Eyewash fountains and safety showers should be available for emergency use.
- Eye Protection:** Do not get in eyes.
Wear chemical goggles.
- Skin and body protection:** Do not get on skin, on clothing.
Wear chemical-resistant protective clothing such as gloves, outer clothing or apron, overshoes and a face-shield suitable to potential exposure.
- Respiratory protection:** Do not breathe vapours or mists.
Use a NIOSH – approved respirator as required to prevent overexposure.
In accord with 29 CFR 1910.143, the types of respirator(s) to be considered include
Air-Purifying Respirator for Organic Vapors.
Full-Face Supplied-Air Respirator.
Self-Contained Breathing Apparatus (SCBA) – for use in environments with unknown concentrations or emergencies.

Exposure Guidelines

Components with workplace control parameters	Regulation	Exposure time	Value	Remarks
Cycloaliphatic amine	ACGIH			None established
Proprietary Component	ACGIH			None established
Phenolic Compound	WEEL	Time Weighted Average (TWA):	10 ppm 44.2 mg/m ³	

9. PHYSICAL AND CHEMICAL PROPERTIES

- Form:** Liquid
- Colour:** Yellow
- Odour:** Amine
- Flash Point:** > 93.33 °C (>199.99 °F) (Closed cup)



TARA PAINTS & CHEMICALS

(An ISO 9001:2015, 18001:2007 Certified Company)

India

A/423/4, Mahagujrat Industrial Estate, Sarkhej Bavla Rd, NH 8A, Village, Moraiya, Gujarat 382213, INDIA
Customer care : +91 8000011774, email : customercare@tarapaints.com, web: www.taralac.com

North America

3106- A, Bethel Road , Upper Chichester – PA 19061
OFFICE : 484 474 0278 EMAIL : karan@tarapaints.com

Solubility in water:

Partially soluble

10. STABILITY AND REACTIVITY

Conditions to avoid:

Avoid high temperatures.

Materials to avoid:

Can react vigorously with strong oxidizing agents, strong lewis or mineral acid, and strong mineral and organic bases.
Reaction with some resins may produce considerable heat and possible violent decomposition.

Hazardous reactions:

Stable under normal use conditions.
Hazardous polymerization will not occur.

11. TOXICOLOGICAL INFORMATION

Acute oral toxicity:

Expected to be moderately toxic, $400 < LD50 \leq 2000$ mg/kg

Acute dermal toxicity:

$1 < LC50 \leq 5$ ml/l.

Chronic Health Hazard

Components	Concentration	Regulation	Value	Remarks
Cycloaliphatic amine		The US. IARC Monographs on Occupational Exposures to Chemical Agents		This component has not been classified by the International Agency for Research on Cancer (IARC)
Proprietary Component		The US. IARC Monographs on Occupational Exposures to Chemical Agents		This component has not been classified by the International Agency for Research on Cancer (IARC)
Phenolic Compound		The US. IARC Monographs on Occupational Exposures to Chemical Agents		This component has not been classified by the International Agency for Research on Cancer (IARC)

Potential Health Effects

Inhalation:

Product is toxic and harmful if inhaled.
May be corrosive to the nose, throat and respiratory tract.
Repeated or prolonged exposure can result in lung damage.
May produce CNS depression.

Skin:

Maybe corrosive (causing chemical burns) which may result in permanent skin damage.
Slightly toxic and may be harmful if absorbed through the skin.
May cause skin sensitization.

Eyes:

May be corrosive to the eyes and may cause severe damage, including blindness.
Vapours may be irritating.



TARA PAINTS & CHEMICALS

(An ISO 9001:2015, 18001:2007 Certified Company)

India

A/423/4, Mahagujrat Industrial Estate, Sarkhej Bavla Rd, NH 8A, Village, Moraiya, Gujarat 382213, INDIA
Customer care : +91 8000011774, email : customercare@tarapaints.com, web: www.taralac.com

North America

3106- A, Bethel Road , Upper Chichester – PA 19061
OFFICE : 484 474 0278 EMAIL : karan@tarapaints.com

- Ingestion:** Maybe moderately toxic if swallowed.
Corrosive and may cause severe and permanent damage to mouth, throat and stomach
May produce CNS depression.
- Aggravated Medical Condition:** Pre-existing eye, skin and respiratory disorders may be aggravated by exposure to this product.

12. ECOLOGICAL INFORMATION

Elimination information (persistence and degradability)

Biodegradability: This section will be updated as ecological reviews are completed.

Eco-toxicity effects

Toxicity to fish: This section will be updated as ecological reviews are completed.

13. DISPOSAL CONSIDERATIONS

Product disposal: If this material becomes waste material, it would be a corrosive hazardous waste, hazardous waste number D002 (40 CFR 262). Refer to the latest EPA or state regulations regarding proper disposal.

14. TRANSPORT INFORMATION

DOT:	UN/NA-No	1263
	Class	8
	Packing group	III
	ERG No.	153
	Proper shipping name	POLYAMINES, LIQUID, CORROSIVE, N.O.S., CYCLOALIPHATIC AMINE (UNMODIFIED)
IMDG:	UN-Number	1263
	Class	8
	Packing group	III
	EMS	F-A S-B
	Description of goods Contains	POLYAMINES, LIQUID, CORROSIVE, N.O.S., CYCLOALIPHATIC AMINE (UNMODIFIED)
IATA Cargo	UN-Number	1263
	Class	8
	Packing group	III
	EMS	F-A S-B
	Description of goods Contains	POLYAMINES, LIQUID, CORROSIVE, N.O.S., CYCLOALIPHATIC AMINE (UNMODIFIED)



TARA PAINTS & CHEMICALS

(An ISO 9001:2015, 18001:2007 Certified Company)

India

A/423/4, Mahagujrat Industrial Estate, Sarkhej Bavla Rd, NH 8A, Village, Moraiya, Gujarat 382213, INDIA
Customer care : +91 8000011774, email : customercare@tarapaints.com, web: www.taralac.com

North America

3106- A, Bethel Road , Upper Chichester – PA 19061
OFFICE : 484 474 0278 EMAIL : karan@tarapaints.com

15. REGULATORY INFORMATION

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

Notification Status

TSCA:	All components listed.
DSL:	All components listed.
EIECS:	All components listed or polymer exempt.
AICS:	All components listed.
ENCS (JP):	All components listed.
INV (CN):	All components listed.
PICCS (PH):	All components listed.
KECI (KR):	All components listed.

CERCLA Hazardous Substances (40 CFR 302)

Cycloaliphatic amine:	No RQ
Proprietary Component:	No RQ
Phenolic Compound:	No RQ

SARA 311/312 Hazards

Acute Health Hazard
Chronic Health Hazard

Emergency Planning and Community Right-To-Know Act (EPCRA) SARA Title III Section 313 Toxic Chemicals (40 CFR 372.65) – Supplier Notification Required

Cycloaliphatic amine:	No De minimis Concentration
Proprietary Component:	No De minimis Concentration
Phenolic Compound:	No De minimis Concentration

Emergency Planning and Community Right-To-Know Act (EPCRA) SARA Title III Section 302 Extremely Hazardous Substance (40 CFR 355, Appendix A)

Cycloaliphatic amine:	Threshold Planning Quantity: No TPQ
Proprietary Component:	Threshold Planning Quantity: No TPQ
Phenolic Compound	Threshold Planning Quantity: No TPQ
Cycloaliphatic amine:	Reportable Quantity: No RQ
Proprietary Component:	Reportable Quantity: No RQ



TARALAC®

TARA PAINTS & CHEMICALS

(An ISO 9001:2015, 18001:2007 Certified Company)

India

A/423/4, Mahagujrat Industrial Estate, Sarkhej Bavla Rd, NH 8A, Village, Moraiya, Gujarat 382213, INDIA
Customer care : +91 8000011774, email : customercare@tarapaints.com, web: www.taralac.com

North America

3106- A, Bethel Road , Upper Chichester – PA 19061
OFFICE : 484 474 0278 EMAIL : karan@tarapaints.com

Phenolic Compound:

Reportable Quantity: No RQ

HMIS Rating:

Health: 3

Fire: 1

Reactivity: 0

16. OTHER INFORMATION

The information provided herein was believed by Epoxy-Coat Inc. to be accurate at the time of preparation or prepared from sources believed to be reliable, but it is the responsibility of the user to investigate and understand other pertinent sources of information, to comply with all laws and procedures applicable to the safe handling and use of the product and to determine the suitability of the product for its intended use. All products supplied by Epoxy-Coat Inc. are subject to Epoxy-Coat Inc.'s terms and conditions of sale.



TARALAC®